

CHASSIS 1 YEAR P.M. SERVICE

All inspection criteria derived from FMCSA CFR49 Part 396 and Appendix G subpart B

UNIT NUMBER	LICENSE NUMBER	OWNER	DATE COMPLETED	FACILITY	MECHANIC'S NAME (PRINT)	SIGNATURE OF MECHANIC
-------------	----------------	-------	----------------	----------	-------------------------	-----------------------

() = INSPECTION
 CODE COLUMN AS INSPECTION IS COMPLETED
 R = MINOR REPAIRS MADE
 SR = SHOP REPAIRS REQUIRED

INSPECT	CODE	REMARKS	LIGHTS	INSPECT	CODE	REMARKS
FRAME & GOOSENECK		1. Bends		25. Test & repair as needed		
		2. Cracks		26. Reflectors, conspicuity tape		
		3. Welds	SUSPENSION	27. U-bolts		
KING PIN		4. Check slider & lubricate		28. Radius Rods, equalizer		
		5. Tap for soundness/cracks		29. Springs & hangers		
		6. Check for wear	AXLES	30. Bent/misaligned		
LOCKING DEVICES		7. Twist locks		31. Cracks		
		8. Index pins		32. Inspect for hub leaks (inc. inner seal)		
		9. Lubricate		33. Add oil to proper level (Oil hubs)		
LANDING GEAR		10. All components in tact		34. Check hub cap tightness		
		11. Tightness of mounts	TIRES & WHEELS	35. INFLATE TIRES: BIAS @ 85 PSI / RADIAL @ 100 PSI		
		12. Operation (turn twice) both speeds		36. 3/32" minimum thread depth		
BUMPERS		13. Lubricate		37. Duals matched within 7/16"		
		14. ICC		38. General condition (dryrot, damaged, etc.)		
BRAKE SYSTEM		Check wheels before releasing brakes!		39. Install metal valve caps (all tires)		
		15a. Manual slack adjusters: Adjust (per MFG spec) Measure & record pushrod travel: LF _____ LR _____ RR _____		40. Check lug nuts for tightness		
		15b. Automatic Slack adjusters: Measure & record pushrod travel: LF _____ RF _____ LR _____ RR _____ (troubleshoot if past limit)	CREDENTIALS	41. Mud flaps, general appearance		
		16. Lubricate cam bushing, slack adjusters		42. License plate		
		17. Brake drums		43. Registration papers		
		18. Brake linings (1/4" minimum)		44. Decals/stencils & markings in place & legible ()		
		19. ABS system	a)	FRONT UNIT #		
		20. Air hoses, air lines, fittings	b)	40/45 FT DECAL/STENCIL (IF EXTENDABLE)		
		21. Gladhands, seals (replace seals if nec.)	c)	FMCSA DECAL		
		22. Relay valves, springbrakes	d)	L.H. SIDE UNIT #		
		23. Drain reservoirs, lubricate drain valves	e)	VIN PLATE		
		24. Air test (Audible leaks)	f)	REAR UNIT #		
			g)	R.H. SIDE UNIT #		
			h)	WEIGHT DECAL		

NOTE: In the event fasteners are found to be loose, retorque per manufacturers recommended settings.

DECLI COPY